

Tubi

Tubi ad **ALTA PRESSIONE PER GRASSO**, in gomma oleoresistente, con rinforzo a 2 treccie di acciaio.
Pressione di esercizio: 400 bar

DIAMETRO 1/4" (Ø interno 6,3 mm)

Art.	lungh. mt.	attacchi
7090	0,5	M-M 10X1
7100	1	M-M 10X1
7105	1,5	M-M 10X1
7110	2	M-M 10X1
7115	2	F-F 1/4"
7018	4	F-F 1/4"
7020	6	F-F 1/4"
7030	8	F-F 1/4"
7040	10	F-F 1/4"
7050	12	F-F 1/4"

DIAMETRO 5/16" (Ø interno 8 mm)

Art.	lungh. mt.	attacchi
7060M	15	F-F 1/4"
7075M	20	F-F 1/4"
7080M	25	F-F 1/4"



Tubi ad **ALTA PRESSIONE PER OLIO**, in gomma oleoresistente, con rinforzo a 1 treccia di acciaio.
Pressione di esercizio: 160 bar.

DIAMETRO 1/2" (Ø interno 12,7 mm)

Art.	lungh. mt.	attacchi
7120	2	F-F 1/2"
7130	4	M-F 1/2"
7140	6	M-F 1/2"
7150	8	M-F 1/2"
7160	10	M-F 1/2"
7170	12	M-F 1/2"

DIAMETRO 5/8" (Ø interno 16 mm)

Art.	lungh. mt.	attacchi
7180F	15	M-F 1/2"
7188F	20	M-F 1/2"
7189F	25	M-F 1/2"



Tubi per **IDROPULITRICI** in gomma, diam. 5/16", 400 bar, 100 °C, attacchi da 3/8" M-F

Art.	lungh. mt.
7017I	3
7060I	15
7075I	20
7080I	25
7081I	30

